DIPLOMAT planter

CARE & MAINTENANCE

Street Design Unit 35 Hayhill Industrial Est

Unit 35 Hayhill Industrial Estate Barrow upon Soar Leicestershire LE12 8LD 01509 815335 sdl@street-design.com www.street-design.com

UK Street Furniture Designers & Manufacturers

General

All Diplomat planter products are manufactured using quality materials, treatments and finishes. The timber components are manufactured from either FSC®-certified treated redwood or FSC®-certified hardwood.

All products require a varied amount of maintenance, depending on the environment, usage and weather conditions. Natural timber will only require cleaning. In time, stained timber will require re-coating.

Maintaining the standard FSC®-certified treated redwood finish

Natural finish pressure treated redwood can be washed down with a mild detergent. More stubborn surface marks can be removed with a light, hand sand with a 120 grit, or higher grade sandpaper. Excessive sanding should be avoided.



Maintaining the standard FSC®-certified hardwood finish

Natural finish hardwood can be washed down with a mild detergent. More stubborn surface marks can be removed with a light, hand sand with a 120 grit, or higher grade sandpaper. Excessive sanding should be avoided.



Maintaining the optional FSC®-certified treated redwood finish

Stained, pressure treated redwood will need to be re-coated after a period of time. The stain can either start to fade, become dull (oxidised) or incur some surface break up. Lightly sand down the timber using a 120 grit, or higher grade sandpaper. We recommend that the timber is re-stained with the original stain colour and manufacturer. Details can be obtained from Street design Limited. Apply the stain evenly, with brush strokes running parallel with the woodgrain, in thin layers, building up the finish as recommended by the stain manufacturer.



Maintaining the optional FSC®-certified hardwood finish

Stained, hardwood will need to be re-coated after a period of time. The stain can either start to fade, become dull (oxidised) or incur some surface break up. Lightly sand down the timber using a 120 grit, or higher grade sandpaper. We recommend that the timber is re-stained with the original stain colour and manufacturer. Details can be obtained from Street design Limited. Apply the stain evenly, with brush strokes running parallel with the woodgrain, in thin layers, building up the finish as recommended by the stain manufacturer.

