MEWS planter

PRODUCT SPECIFICATION

Street Design Limited

Unit 35 Hayhill Industrial Estate Barrow upon Soar

145 x 45mm FSC treated redwood or FSC iroko hardwood

Galvanised 60 x 60 x 5mm mild steel corner brackets or Dull polished 60 x 60 x 3mm st grade 304 stainless steel

95 x 95mm FSC treated redwood or FSC iroko hardwood

Galvanised mild steel or dull polished stainless steel

All planters are guaranteed for 15 years minimum

775

607

1065

897

34

41

11

920

752

1210

1042

39

47

11

corner brackets

Natural

Stained

100 x 47mm FSC treated redwood

Polyester powder coated mild steel

Adjustable feet on a mild steel frame

Trellis panels and pergola structures

630

462

Tree anchor fittings

Watering systems

Base skirting boards

Inner tower planters

Bench seating

LED lighting

485

317

M12 size - bright zinc plated

18mm FSC treated Eucalyptus plywood

Leicestershire LE12 8LD

Contact us:

Telephone: 01509 815335 01509 815332 Fax:

Email: sdl@street-design.com Web site: www.street-design.com







Construction

All Street Design products are designed and manufactured using only quality. durable materials, construction details and fixings, to provide a long-lasting, durable life expectancy.

Assembly

Planters up to 2.8 x 2.8m will be delivered to site fully assembled for off loading and positioning on site. Planters larger than 2.8m will be supplied in sections for bolting together on site.

Materials

Hardwood planters are constructed from FSC iroko hardwood, from sustainable sources. Softwood planters are constructed using FSC European redwood that has been Wolmanit CX treated, for a desired service life of 30 years minimum. All mild steel fixings will be M12 size and have a bright zinc plated finish. Planters will be fitted with a Terram 1000, geotextile filter fabric lining, which allows the water to drain through the planter. while retaining the fill material.

Standard finish

FSC treated softwood and iroko hardwood will be left natural to reduce the need for re-staining and help reduce maintenance costs.

Optional finish

If required, timber planters can be supplied with a stained finish using 3 coats of quick drying water based wood stain, to the colour of you choice. Material samples available on request.

Options

Mews planters are manufactured to order. Before we can manufacture the planters. we need to know the following:

- plan size and shapes
- heights
- material
- finish
- details of accessories required

Accessories

To enhance your Mews planter and create a product that is suitable for your specific application, you can add from a range of planter accessories.

- Tree anchors
- · Adjustable feet
- Watering system
- Integral bench seating
- Inner tower planters
- LED lighting
- · Internal steel frame
- Base skirting
- Pergola structures
- Trellis panels
- Plagues

FSC natural iroko hardwood with optional Henley bench benches



FSC natural treated redwood with galvanised corner brackets



Large FSC natural treated softwood planters

Technical information

10011111001 IIIIO11110011
Material
Horizontal walling slats
External corner detail
Internal corner posts
Base bearers
Base flooring
Fixings
Standard finish - timber
Optional finish - timber
Standard finish - metal
Optional finish - mild steel
Accessories

Guarantee Walling heights (mm)

Planting depths (mm) Weights

FSC treated redwood (kgs / linear m.) FSC iroko hardwood (kgs / linear m.) FSC treated base (kgs/m²)

Light fill material can be based on: Heavy fill material can be based on:

14 19 24 29 18 23 29 35 11 11 11 11 1000 kgs / m³

2000 kgs / m³

Timber policy

All treated softwood planters are manufactured using materials obtained from growers who operate under the Forest Stewardship Council (FSC).

All iroko hardwood planters are manufactured using materials obtained from growers who operate under the Forest Stewardship Council (FSC).