MEWS planter

MATERIAL FINISHES

Street Design Limited

Unit 35 Hayhill Industrial Estate Barrow upon Soar Leicestershire LE12 8LD Contact us:

Telephone: 01509 815335 01509 815332 Fax: Email: sdl@street-design.com Web site: www.street-design.com





Standard finish

FSC certified treated redwood standard finish

As standard, all FSC treated redwood planters will be supplied with a natural finish. The preservative treatment process will colour the timber a light brown/green.



Stainless steel standard finish

After fabrication, the 60x60mm stainless steel angle corner brackets will be dull polished. The stainless steel corner brackets will require no further maintenance.



Aged natural treated redwood

Left to weather naturally, the timber will eventually turn a silver grey colour.



Optional finish at extra cost

FSC certified treated redwood wood optional finish

As an optional extra, the FSC treated redwood can be supplied with a stained finish. This will be applied after the timber treatment process. The standard stain will be 3 coats of Ronseal guick drying water based stain. The standard colour will be teak. Other stains and colours can be applied upon request.



Optional grey stained finish


FSC certified iroko hardwood standard finish

As standard, all FSC iroko hardwood planters will be supplied with a natural finish. Due to the nature of the material and the density of the grain, iroko hardwood is not capable of taking a preservative treatment. Iroko hardwood is a naturally durable material, giving a life expectancy in excess of a treated softwood.



FSC certified iroko hardwood optional finish

As an optional extra, the FSC iroko hardwood planters can be supplied with a stained finish. The standard stain will be 3 coats of Ronseal guick drying water based stain. The standard colour will be teak. Other stains and colours can be applied upon request.



Optional teak stained finish



Optional polyester powder coated finish

Aged natural iroko hardwood

Left to weather naturally, the timber will eventually turn a silver grey colour.



Mild steel standard finish

After fabrication, the 60x60mm angle corner brackets will be hot dip galvanised. The galvanised corner brackets will require no further maintenance.



Mild steel optional finish

After fabrication and hot dip galvanising, the 60x60mm angle corner brackets can be polyester powder coated. They can be powder coated to any RAL colour depending on product quantity and stock levels of powder colours. Depending on stock levels the powders are available in 3 gloss levels; gloss, satin and matt.